













Salient Features

- It is designed to withstand high wear and tear resistance having a wear layer of 0.20 mm
- Available in wood and marble designs
- Natural wooden surface textures
- Application areas: shops, hotels, residences, offices, malls, schools etc.

DIMENSIONS AVAILABLE

Thickness	1.6 mm
Roll width	2 mtr
Roll length	20 linear mtr

PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	SYMBOLS	TEST METHOD	RESULTS
TOTAL WEIGHT		EN 430	2.85 KG/ MTR2
THICKNESS OF WEAR LAYER		EN 429	0.20 MM
ABRASION RESISTANCE		EN 660-2 EN 649	WEAR GROUP M
DIMENSIONAL STABILITY (%)		EN 434	≤0.4%
FLEXIBILITY AT LOW TEMPERATURE		EN 435	SHALL NOT BREAK, CRACK OR SHOW ANY OTHER SIGN OF FAILURE
RESIDUAL INDENTATION AFTER STATIC LOAD		EN 443	≤0.10 MM
CASTOR CHAIR		EN 425	SUITABLE/CONTINUOUS USE
COLOUR FASTNESS TO DAY LIGHT		ISO 105-BO5	>BLUE WOOL STANDARD 5
RESISTANCE TO CHEMICAL			PRODUCT ARE NORMALLY RESISTANT TO DILUTED ACIDS & ALKALIS
SURFACE SPREAD OF FLAME		BS 476 PART 7	CLASS 1
SLIP RESISTANCE		DIN 51130	R 9
PERFORMANCE CLASSIFICATION		EN 685	32