













SALIENT FEATURES

- They are 'P' rated and have a slip resistance of R9
- Available in rolls or tiles
- The floorings are embossed with "Raindrop" embossing design which enables quick cleaning & easy maintenance.
- Robust Ultima (2.0 mm) is available with PUR (Polyurethane) surface protection providing resistance against scratches & dirt accumulation and also ensures quick cleaning/ mopping
- Can be thermo welded for joint free installation
- Application areas : Offices, Shops, Factories, Porta Cabins, Auditoriums, schools, libraries, healthcare etc.

DIMENSIONS AVAILABLE

Thickness	1 mm, 1.5 mm, 2 mm, 3 mm
Roll width	1.50 mtr, 2 mtr
Roll length	15 linear mtr, 20 linear mtr
Tile size	305 mm x 305 mm

PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	SYMBOLS	TEST METHOD	RESULTS
TOTAL WEIGHT		EN 430	3.40 KG /SQ. FOR 2.00 MM
DIMENSIONAL STABILITY		EN 434	≤0.40%
RESIDUAL INDENTATION AFTER STATIC LOAD		EN 433	≤0.10MM
FLEXIBILITY		EN 435	40 MM MANDREL, PASSED
ABRASION RESISTANCE		EN 660-2 EN 649	WEAR GROUP P
SURFACE SPREAD OF FLAME		BS 476 PART 7	CLASS 1
FIRE PROPAGATION		BS 476 PART 6	(I)=10.8 } CLASS "O" (II)=1.7 }
HYGIENE			TEST RESULT DEMONSTRATES THAT IT INHIBITS GROWTH OF MICROBES
COLOUR FASTNESS TO DAY LIGHT		ISO 105-BO2	>BLUE WOOL STANDARD 5
SLIP RESISTANCE		DIN 51130	R 9
BEARING A CASTOR CHAIR		EN 425	SUITABLE/CONTINUOUS USE
RESISTANCE TO CHEMICALS		EN 423	NO VISIBLE CHANGE
SOUND ABSORPTION		ISO 140-8 EN ISO 717-2	Δ LW = 5db
PERFORMANCE CLASSIFICATION		EN 685	34, 41